

SHANTUI

SK135 Mining Truck



| | |
|--------------|-----------------------|
| Engine Model | Weichai WP15HG770E304 |
| Power/Speed | 566 kW/1900 rpm |
| Total mass | 135,000 kg |
| Case volume | 50 m ³ |

Value that works

SK120 SPECIFICATIONS

| SK135-G | | |
|--------------------|------------------------------------|---|
| Vehicle parameters | Total mass(kg) | 135000 |
| | Load capacity(kg) | 90000 |
| | Length×Width×Height(mm) | 10250×4000×4450 |
| | Drive type | 6×4 |
| | Case volume(m3) | 50 |
| | Axle distance(mm) | 4665+1830 |
| | Wheelbase(mm) | 2890(front 3200) |
| | Max-speed(km/h) | 42 |
| | Gradeability(%) | 30 |
| | Min turning diameter(m) | 28 |
| Axle load | Ground clearance(mm) | 380(Lower front axle) |
| | Fully loaded(t) | 30000 |
| Engine | Model | WP15HG770E304 |
| | Power/Speed(kW r/min) | 566/1900 |
| | Torque/Speed(N*m /rpm) | 2800/ (1200-1600) |
| Clutch | Type | 400 Double plate pull type diaphragm spring clutch assembly |
| Gearbox | Model | 8DS280A+FHB400A |
| Drive axle | Type | Central, hub planetary three-stage reduction, with inter-axle differential lock |
| | Rated axle load(kg) | 50000 |
| Air filter | Type | Double channel desert air filter |
| Radiator | Structure | Plate-Fin |
| Fuel system | Capacity(L) | 800 |
| Steering system | Power steering | Full hydraulic steering |
| | System pressure(MPa) | 17 |
| | Flow(L/min) | 50 |
| Braking system | Service brake | Double-circuit drum type air brake |
| | Parking brake | Spring energy-storage air-break braking, with emergency braking |
| | Auxiliary brake | Engine cylinder brake |
| | System pressure(bar) | 10 |
| | Standing slope(°) | 15 |
| Suspension | Front suspension | Oil and gas suspension |
| | Leaf spring thickness/width/number | 180*150*220 |
| | Rear suspension | Leaf spring balance suspension |
| | Leaf spring thickness/width/number | 32/120/15 |
| CAB | Type | Single side narrow body cab |
| | Damping seat | Upward/downward, forward/rearward adjustable, backrest angle adjustable |
| Frame | Type | High-strength steel flexible frame |
| Wheel | Tyre model | 16.00R29 ★★★ |
| | Rim model | 11.5/2.5-29 |

* THE SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. THE PICTURES MAY INCLUDE OPTIONS. THE ACTUAL COLOR & APPEARANCE OF THE PRODUCT MAY DIFFER FROM WHAT IS SHOWN.



Shantui Social

SHANTUI CONSTRUCTION MACHINERY CO., LTD.

ADD: No. 58, G327 Highway, Jining City, Shandong, CHINA
 TEL: +86-537-2909369
 FAX: +86-537-2311219
 EMAIL: trade@shantui.com
 WEB: www.shantui.com

SHANTUI
 VALUE THAT WORKS