

TUBOSHU⁷

SPECIFICATIONS SHEET

ELECTRIC ARTICULATING BOOM LIFT TAB250.22E-H



TUBOSHU

SUITE 5, 66 WESTBOURNE TERRACE
LONDON, ENGLAND W2 3UJ
T: +44 7457 405 800

TUBOSHU.CO.UK

CHARACTERISTICS		
Manufacturer		TUBOSHU
Model		TAB250.22
Configuration Number		JA20JE
SIZE		
Max. Working Height	m	22.1
Platform Height Max.	m	20.1
Horizontal Outreach	m	11.6
Up and Over Height	m	8.2
Platform (Length x Width)	m	1.83 x 0.76
Stowed Length A	m	9.6
Overall Length B	m	2.46
Stowed Length C	m	2.53
Wheelbase D	m	2.5
Ground Clearance E	m	0.44
Turning Radius (Inside/Outside)	m	3.4/5.4
Tire Models		355/55D625
PRODUCTIVITY		
Platform Capacity	kg	250
Max. Platform Occupancy		2
Gradeability	%	40
Drive Speed (Stowed)	km/h	4.8
Drive Speed (Raised)	km/h	1
Max. Work Slop	°	3/5
Platform Rotation	°	180
Jib Swing Angle	°	130
Turntable Rotation	°	360 (discontinuous)
POWER & WEIGHT		
Battery Voltage/Capacity		48V / 480Ah
Charger Output Current		48VDC / 60A
AC Driving Motor		23VAC/3.3kw x 4
Ac Feature Motor		31VAC/12kw
Emergency Power Unit		12VDC/2.2kw
Machine Weight	kg	9500

STANDARD ITEMS	
◇	Four-Wheel Drive
◇	Two-Wheel Steering
◇	Proportional Joystick Controls
◇	Self-Leveling Platform
◇	180° Left and Right Swing Platform
◇	Front Oscillating Axle
◇	Tilt Alarm
◇	Flash
◇	Horn
◇	Hour Meter
◇	360° Turntable Rotation (Discontinuous)
◇	Positive Traction Four Wheel Drive
◇	Fault Diagnosis System
◇	12V DC Auxiliary Power
◇	Lead-Acid Battery 48V480Ah
◇	Lithium Battery 48V460Ah (Optional)
◇	AC Feature Motor 31VAC/12kw
◇	AC Driving Motor 32VAC/3.3kw×4
◇	Standard Container Transport

