

TUBOSHU⁷

SPECIFICATIONS SHEET

STACKER TS20E-H ELECTRIC



TUBOSHU

SUITE 5, 66 WESTBOURNE TERRACE
LONDON, ENGLAND W2 3UJ
T: +44 7457 405 800

TUBOSHU.CO.UK

CHARACTERISTICS			
Manufacturer		TUBOSHU	
Model		TS20-E	
Configuration Number		CDD20-D930	
Mast Type		2-Stage	
Operatibg Type		Walkie/Stand On	
Load capacity	kg	2000	
Load center	mm	600	
Wheel Base	mm	1325	
WHEELS			
Wheel type		PU	
Wheel Quantity (driving wheel, balance wheel, bearing wheel)		1/2/4	
Driving Wheel Size	mm	ø248 × 75	
Balance Wheel Size	mm	ø115 × 55	
Bearing Wheel Size	mm	ø84 × 70	
DIMENSION			
Standard Lift height	mm	1400/2000/2500/3000/3300/3600/4000	
Max. Extend Height	mm	1900/2500/3000/3500/3800/4100/4500	
Mast Lowered Height	mm	1185/1535/1765/1980/2135/2335/2500	
Lowered Fork Height	mm	90	
Fork Size (length/width/thickness)	mm	1150(1220)/185/55	
Overall Length	mm	2050/2470	
Overall Width	mm	856	
Min. Turning Radius	mm	1580/1990	
Min. Aisle Width for Pallets 800x1200	mm	2180/2580	
Min. Aisle Width for Pallets 1000x1200	mm	2210/2600	
Min. Ground Clearance	mm	30	
PERFORMANCE			
Travel Speed Laden/Unladen	km/h	6/6	
Lift Speed Laden/Unladen	mm/s	130/180	
Lowering Speed Laden/Unladen	mm/s	100/200	
Gradeability Laden/Unladen	%	6/8	
ELECTRICAL CONFIGUARTION			
Drive Motor/Lift Motor/Steering Motor	kW	AC1.5/DC3/DC0.15	
Brake		Electromagnetic/Regenerative	
BATTERY			
		LEAD-ACID BATTERY	LITHIUM BATTERY (optional)
Battery Voltage / Capacity	V/Ah	24/280	24/200
Controller		ZAPI	ZAPI
Battery Weight	kg	235	99
Service Weight (with battery)	kg	1213	1077