

SPECIFICATIONS SHEET

TOW TRACTOR TT 300E-H ELECTRIC

With a towing capacity of 30 tons, this electric tow tractor is a robust and efficient machine designed to handle demanding loads effortlessly. Its durable build and advanced electric powertrain ensure smooth, reliable performance while navigating challenging environments, making it an ideal choice for both indoor and outdoor applications.



TUBOSHU

SUITE 5, 66 WESTBOURNE TERRACE LONDON, ENGLAND W2 3UJ **T:** +44 7457 405 800



CHARACTERSTICS					
Manufacturer		TUBOSHU			
Model		ТТ300-Е			
Configuration Number		QYD300-A1Li			
TECHNICAL PARAMETER					
Driving Mode		Seated			
Rated Towing Weight	Т	30			
Service Weight, Including Cab / Excluding Cab	kg	3670/3460			
Rated Traction Force	kN	14			
Max. Traction Force	kN	29			
Travelling Speed (loaded/unloaded)	km/h	11/26			
Gradeability (loaded/unloaded)	%	4/30			
Overall Dimension LxWxH (including rear traction base and cab)	mm	3230x1425x1980			
Wheelbase	mm	1990			
Tread Front	mm	1160			
Tread Rear	mm	1160			
Min. Steering Radius	mm	3000			
Min. Ground Clearance	mm	150			
Traction Hook Height	mm	425			
Tyre Front		6.50-10-10PR			
Tyre Back		29x9-15-14PR			
Service Brake		Hydraulic Power Assisted Brake			
Parking Brake		Mechanical Brake			
Driving Type		Rear Drive			
Driving Motor Power	kW	28.7 (AC)			
Steering Motor Power	kW	1.35			
Battery Voltage/Capacity	V/Ah	80/813			
Driving Control Mode		Electronic Stepless Mode			
Operator's Ear Noise	dB	<70			

STANDARD CONFIGURATIONS				
Double Chamber Dual Loop Brake	Rear View Mirror	Liquid Crystal Combined Instrument		
Suspension Bridge with Front & rear Suspension	Moon White Paint	Lithium Battery		
Integrated Drive Bridge	Pneumatic Tyre	Self Locking Traction Mechanism		
Fully Enclosed Cab				

OPTIONAL CONFIGURATIONS			
Battery Extinguishing Device	Warm Air Blower	Air Conditionner	
Solid Tyre	Warning Lamp	Fully Enclosed Front Window Driving Cab	
Battery Double Charge	Front Traction Base	Battery 80V/808Ah (HEDING)	

TUBOSHU.CO.UK