

## SPECIFICATIONS SHEET

## WHEEL LOADER TW640D-S DIESEL

With a bucket capacity of 4 cubic meters and an operating weight of 22,500 kilograms, this robust machine is designed to effortlessly manage heavy loads and navigate challenging terrain.



TUBOSHU

SUITE 5, 66 WESTBOURNE TERRACE LONDON, ENGLAND W2 3UJ **T:** +44 7457 405 800

CHARACTERSTICS			
Manufacturer		тивозни	
Model		TW640	
Configuration Number		L68K-B5	
ENGINE			
Emission Regulation		Tier 2 / Stage II	
Make		WEICHAI	
Model		WD10G240E201	
Rated Power		178kW @ 2200 rpm	
Max Torque	N.m	1000	
Displacement	L	9.726	
Cylinders		6	
Aspiration		Turbocharged	
LOADER ARM PERFORMANCE			
Tipping Load - Full Turn	kN	137 kN	
Bucket Breakout Force	kN	205 kN	
Maximum Dump Angle at Full Height	0	45	
Dump Clearance at Full Height Discharge	mm	3480 mm	
Dump Reach at Full Height Discharge	mm	1300 mm	
Maximum Hinge Pin Height	mm	4718 mm	
Maximum Dipping Depth, Bucket Level	mm	80 mm	
Bucket Capacity	m³	3.5	
Operating Weight	kg	22,500	
TRANSMISSION			
Transmission Type		Planetary, power Shift	
Torque Converter		Single Stage, Four Elements	
Maximum Travel Speeds FWD	km/h	37	
Maximum Travel Speeds REV	km/h	16	
Number of Speeds FWD		2	
Number of Speeds REV		1	
AXLE			
Differential Front Type		-	
Differential Rear Type		-	
Axle Oscillation	•	±12	
STEERING			
Steering Configuration		Articulated	
Steering System Pressure	Mpa	18	





TUBOSHU.CO.UK

BRAKES			
Service Brake Type		Caliper Disk Brake	
Service Brake Actuation		Air Over Hydraulic	
Parking Brake Type		Air Brake	
Parking Brake Actuation		Mechanical	
TYRES			
Tire Size	mm	26.5-25	
HYDRAULIC SYSTEM			
Main Pump Type		Gear	
Main Relief Pressure	Mpa	21	
Raise Time	S	5.3	
Total Cycle Time	S	9.97	
SERVICE CAPACITY			
Fuel Tank	L	330	
Hydraulic Oil Tank	L	255	
Engine Oil	L	21	
Axles, Each	L	41 x 2	
Transmission	L	45	
Antifreeeze	L	80	
DIMENSIONS			
Length	mm	9320	
Width	mm	3080	
Height	mm	3570	
Wheelbase	mm	3500	
Wheel Tread	mm	2250	
Ground Clearance	mm	510	
Turn Angle, Either Side	•	35	
Turning Radius, Outisde of Tire	mm	6955	
Turning Radius, Center of Tire	mm	6675	
Turning Radius, Bucket Carry	mm	7686	
Maximum Raise Height	mm	4718	



